

## Fireproof Aluminium Composite Panel

### Specifications of fireproof aluminium composite panel

ALLUWELL ® FR	Width	1000mm	1220mm	1250mm	1500mm	1575mm	2000mm
3mm / 4mm	Length	2000-6000mm	2000-6000mm	2000-6000mm	2000-6000mm	2000-6000mm	2000-6000mm
Solid Colours	<input type="checkbox"/>	■	■	■	■	■	-
Metallic Colors	<input type="checkbox"/>	■	■	■	■	■	-
Sparkling colors	<input type="checkbox"/>	■	■	■	■	■	-
Wood designs	<input type="checkbox"/>	-	■	■	■	-	-

### Technical data of fireproof aluminum composite panel

Hardly flammable	DIN 4102,Part1		Class B1
Class B1 Fireproof ACP	ASTM E84-05	Flame spread index	5
		Smoke developed index	0
Min. rest length of burning	GB/T 8625-88	≥0mm	330mm
Average rest length of burning	GB/T 8625-88	≥150mm	422mm
	DIN 4102,Part1	-	370mm□480mm
Smoke temperature	GB/T 8625-88	≤200°C	187°C
	DIN 4102,Part1	-	123°C□160°C
Flame tip's height	GB/T 8625-88	□150mm	15mm
Smoke density grade	GB/T 8627-1999	≤75	11
	DIN 4102,Part1	≤400%min	10%-16%min

## FEED BACK FORM

E-mail:

Message:

Product Name:

Your Name:

Company:

FAX / TEL:

MSN/SKYPE

Address: